

CLAIMS

1. *(currently amended)* An apparatus comprising:
a plurality of logically independent processors;
~~a system-processor bus;~~
~~a power board;~~
~~a heat spreader;~~ and
a cache control and bus bridge device in communication with
the plurality of processors such that it is logically interposed
between the processors and the ~~system-processor bus~~, and wherein
the processors and cache control and bus bridge device ~~and power~~
~~board and heat spreader~~ are disposed in a module form factor such
that the apparatus is a drop-in replacement for a standard single-
processor module.
2. *(currently amended)* The apparatus of claim 1 wherein
the processors are IPF ~~packaged~~ processors.
3. *(original)* The apparatus of claim 1 wherein a volume of
the module form factor is less than or equal to a volume of a
standard single-processor module.
4. *(currently amended)* The apparatus of claim 3 ~~wherein~~
the standard single-processor module is an ITANIUM 2 module.
5. (canceled)
6. *(currently amended)* The apparatus of claim ~~5-1~~
wherein the processors and cache control and bus bridge device are
disposed on a processor board, and wherein the heat spreader is
piggybacked onto the power board and the power board is
piggybacked onto the processor board.

7. *(original)* The apparatus of claim 6 wherein the power board is disposed between the processor board and the heat spreader and wherein a plurality of pedestals on the heat spreader extend through a plurality of holes in the power board thereby contacting one or more of the processor packages and cache control and bus bridge device such that both the processor board and the power board contact the heat spreader.

8. *(original)* The apparatus of claim 7 wherein the pedestals each comprise a variable-gap thermal interface.

9. *(original)* The apparatus of claim 8 wherein at least one variable gap thermal interface is a piston and spring thermal interface.

10. *(original)* The apparatus of claim 9 wherein at least one variable gap thermal interface has a tolerance of 60 mils.

11. *(original)* The apparatus of claim 1 further comprising a power board disposed in the module form factor, wherein the processors and cache control and bus bridge device are disposed on a processor board, and wherein the power board is piggybacked onto the processor board, and wherein a plurality of components of both the power board and processor board are arranged in a complementary skyline and interleaved component fashion.

12. *(currently amended)* The apparatus of claim 1 further ~~comprising a power board disposed in the module form factor;~~ wherein the power board utilizes power limiting architecture.

13. *(original)* The apparatus of claim 1 further comprising flexible power cable routing within a volume of the form factor.

14. *(currently amended)* The apparatus of claim 1 wherein the apparatus is included in a computing device comprising a plurality of similar apparatuses in communication with ~~the a system~~ bus.

15. *(original)* The apparatus of claim 1 further comprising a power board and a processor board, wherein the processors and cache control and bus bridge device are disposed on the processor board, and wherein the power and processor boards employ microvias, accommodated within areas of one or more conductive pads, to provide high current capacity, low impedance paths from surfaces of those boards to a plurality of buried vias and traces in underlying layers of those boards.

16. *(currently amended)* A method comprising:
connecting on a local bus a plurality of processors such that the processors are logically independent;

logically interposing between the local bus and a ~~system processor~~ bus an in-line cache control and bus bridge device;

disposing in a module conforming to a standard single-processor module form factor the plurality of processors, the local bus, and the in-line cache control and bus bridge device, ~~said module comprising a piggyback power supply and a heat spreader;~~
and

operating the plurality of processors and the in-line cache control and bus bridge device such that data input to each of the processors is processed independently and simultaneously.

17. *(currently amended)* The method of claim 16 wherein the operating the plurality of processors comprises:

- connecting the module to a system board through an interface compatible with a standard single-processor module;
- interfacing the system board to a computer system platform;
- inputting data to the module from the system board via a system bus;
- processing the data by a plurality of processors such that each processor processes some of the data independently and simultaneously to the other processors of the plurality; and
- receiving by components in the system board processed data from the module via the system bus.

18. *(canceled)*

19. *(currently amended)* The method of claim ~~18~~ 16 wherein the power supply comprises a board on which is disposed a plurality of components packed more densely than power components in a power board associated with a single-processor module.

20. *(original)* The method of claim 16 further comprising managing a power consumption of the module at a rate equal to or less than a power consumption of a standard single processor module.

21. *(original)* The method of claim 20 wherein managing comprises changing a state of the processors from a multi-issue mode to a single-issue mode.

22. *(original)* The method of claim 20 wherein managing comprises lowering an operating frequency of the processors while maintaining a performance of each of the processors such that the processors together produce a performance equal to or better than that of a standard single-processor module.

23. *(original)* The method of claim 20 wherein the processors together produce a performance of 1.5-2.0 times that of a standard single-processor module.

24. *(original)* The method of claim 20 wherein a unit performance per Watt is kept at a maximum for the processors.

25. *(original)* The method of claim 16 wherein operating the plurality of processors comprises exchanging data between the processors and a plurality of system components adapted to communicate with a single processor module such that the system components communicate with the plurality of processors as if the system components were communicating with a single-processor module.

26. *(original)* The method of claim 16 wherein conforming to a standard single-processor module form factor comprises having a footprint of an area not greater than that of a standard single-processor module and having a volume not greater than that of a standard single-processor module.

27. *(previously presented)* A system comprising:
a plurality of processors mounted onto a processor board;
a power board;
a heat spreader disposed with the plurality of processors and the power board in a first module conforming to a standard single-processor module footprint, wherein the power board is piggybacked with regard to the processor board, wherein the heat spreader is piggybacked with regard to the power board, and wherein the heat spreader thermally contacts the power board and the processor board;
a computer system; and
a system board adapted to communicate with the computer system and comprising an interface adapted to communicate with a standard single-processor module, wherein the first module is coupled to the system board and is in communication with the system board and the computer system.

28. *(original)* The system of claim 27 wherein the computer system is a server.

29. *(original)* The system of claim 27 wherein the processor board comprise an in-line cache control and bus bridge device and a fourth level external cache coupled to the in-line cache control and bus bridge device.

30. *(original)* The system of claim 27 wherein the first module is a drop-in replacement for a single-processor module.

31. *(original)* The system of claim 27 wherein the first module is coupled to the system board by a wedgelock device.

32. *(original)* The system of claim 27 further comprising a cooling strap, wherein the cooling strap and the heat spreader comprise a common interface thermal solution.

33-35. *(canceled)*

36. *(currently amended)* A multi-processor module comprising:

a plurality of processors;

a piggybacked power board;

a heat spreader; and

a cache control and bus bridge device that controls access to a common cache by the plurality of processors and electrically isolates the processors from a system bus, said cache control and bus bridge device is being adapted to exchange data between the processors and a plurality of system components adapted to communicate with a single processor module such that the system components communicate with the plurality of processors as if the system components were communicating with a single-processor module.

37. *(original)* The multi-processor module of claim 36 wherein the module is compatible with a single-processor module interface.

38. *(currently amended)* The multi-processor module of claim 36, wherein the processors are IPF packaged processors.

39. *(canceled)*

40. *(currently amended)* The multi-processor module of claim 36, wherein said first module is a drop-in replacement for a single-processor module.

41. *(original)* A system comprising:

means for connecting a module to a system board through an interface compatible with a standard single-processor module;

means for interfacing the system board to a computer system platform;

means for inputting data to the module from the system board via a system bus

means for processing the data by a plurality of processors such that each processor processes some of the data independently and simultaneously to the other processors of the plurality; and

means for receiving by components in the system board processed data from the module via the system bus.

42. *(original)* The system of claim 41 further comprising means for managing a power consumption of the module at a rate equal to or less than a power consumption of a standard single processor module.

43. *(original)* The system of claim 41 further comprising a fourth level external cache included in the module and accessible by the plurality of processors.

44. *(original)* The system of claim 41 wherein the means for processing the data by a plurality of processors comprises means for exchanging data between the processors and a plurality of system components adapted to communicate with a single processor module such that the system components communicate with the plurality of processors as if the system components were communicating with a single-processor module.

45. *(previously presented)* The system of claim 27, wherein said processors are in communication with a cache control and bus bridge device that is interposed between said processors and a system bus.

46. *(previously presented)* The apparatus of claim 1 further comprising a plurality of multi-processor modules in communication with said system bus.

47. *(canceled)*

48. *(new)* An apparatus comprising a processor module including:

- a processor board;
- plural processor packages mounted on said processor board;
- a bridge device for communicatively coupling said processor packages with a system bus, said bridge device being communicatively coupled to said processor packages; and
- one or more connectors for attaching said processor board to a system board incorporating said system bus so that said system bus is communicatively coupled to said bridge device.

49. *(new)* A processor module as recited in Claim 48 further comprising:

- a power board fixed to said processor board; and
- one or more power converters mounted on said power board.

50. *(new)* A processor module as recited in Claim 49 wherein said processor board, said power board, said processor packages, said one or more power converters, said bridge device, and said one or more connectors are arranged so as to conform to a form factor associated with a standard single-processor module.

51. (*new*) An apparatus as recited in Claim 49 wherein the number of power converters exceeds the number of processor packages.

52. (*new*) An apparatus as recited in Claim 48 further comprising said system board and one or more additional processor modules attached to said system board, each of said modules including one or more processor packages, said processor modules communicating with each other via said system bus.